

PO Box 93115, Southlake, TX Toll Free: 1 888 424-1740 Fax#: 817 424-1745

Nylon Finger Trap

Finger Traction Device



Rx Only



REF: K-100-XS, K- 150-XS, K-200-S, K-250-S, K-300-M, K-350-M, K-400-L K-450-L, K-500-XL, K-550-XL, K-650, K-750

<u>How to Use:</u> Place patient's fingers in finger traps. Once fingers are secure in traps, place the loop of the finger trap in the appropriate clip on ISI's Digi Grip or other traction device. The traction device may be suspended from an IV pole or traction system.

You may also use ISI's Digi Grip, Traction Strap and weight set for additional patient stability.

DG-3000	Digi Grip
DG-7550	Digi Grip System
WS1820	Traction Strap
S Hook	Stainless Steel S Hook
0350	½ pound (.023 Kilogram) weight
0352	1 1/2 pound (.068 Kilogram) weight
0354	2 1/2 pound (1.13 Kilogram) weight
0357	5 pound (2.27 Kilogram) weight

Sterilization instructions: Clean with any standard disinfectant prior to sterilization.





Sterilize the finger trap before each use.

1. Steam Sterilization General Instructions:

Follow standard hospital sterilization practices

- A. Place clean instruments in an instrument tray
- B. If instruments are to be wrapped, two double thicknesses of #140 thread count wrappers should be utilized. Exposure times are the same for wrapped or unwrapped instruments
- C. Follow the instructions for the gravity air displacement steam sterilization listed below

IFU – 028 Nylon Finger Trap

Page 1 of 2

Revision: A

2. Gravity Steam Sterilization:

- A. Double wrap in standard central supply wrap.
- B. Set the temperature and corresponding exposure time:
 121-123 degrees Celsius for 30 minutes

After cleaning, store in accordance with standard hospital operating procedures to maintain cleanliness. Inspect finger trap before and after each use.

If the Finger Trap is split or frayed, **DO NOT USE**. Handle and dispose of in accordance with accepted medical practice and applicable laws and regulations.



EMERGO EUROPE Molenstraat 15

2513 BH, The Hague The Netherlands

Tel: +31 (0)70 345 8570 Fax: +31 (0)70 346 7299

Symbol	Explanation
***	Manufacturer
EC REP	European Authorized Representative
NON STERILE	Non-Sterile
REF	Catalogue Number
\triangle	Caution, Consult Accompanying Documents

Explanation of Symbol